

224 - SEALING OIL

SEALING OIL for wood-outdoor made for treatment and maintenance of outdoor wooden surfaces, such as garden furniture, porches, and oil-finished building structures. The oil is suitable for all types of wood, from exotic woods like teak, merbau, or mahogany, to pine, beech and oak. The oil penetrates the surface, seals it, and provides a lasting protection against drying out, moisture and dirt. The natural colour and structure of the wood will be amplified.

Instructions

Apply the oil with a brush or cloth in a generous and even layer. Very absorbent surfaces should be treated several times until the surface is saturated. Wipe off excess oil after 1 hour. Clean the brush first in turpentine, then in soap water. **Coverage:** 8-12 m² pr. litre. **Drying time:** about 24 hours.

Declaration

DANGER: Contains: Aliphatic hydrocarbons: may be fatal if swallowed and enters airways. Isophthalic alkyds, agent to prevent rot and fungi, lead-free siccative and antioxidants. Contains 3-iodo-2-propynyl butylcarbamate: May produce an allergic reaction.

WARNING: Used rags may self-ignite and should therefore be soaked in water and packed air-tight in aluminium foil or in a plastic bag before discarding. Keep out of reach of children.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. If medical advice is needed, have product container or label at hand.



Conditioning

500ml / 1000ml / 2500ml / 5000ml

If you have any questions, please contact our Technical Department on: +45 4817 6970